

Maximum Width		3000mm
Maximum Drop		2800mm
Maximum Area		8.4 sqm
Maximum Tape Spacing		650mm
End Route	- Standard	150mm
Slat Spacing		20mm
Slat Overlap		5mm
Head Channel	- Width - Height - Thickness - Material - Finish	28mm 20mm 0.55mm Zincalume Oven-baked modified Polyester over appropriate chemical pre-treatment.
Bottom Rail	- Width - Depth - Thickness - Material - Finish	20mm 10mm 0.55mm Zincalume Oven-baked modified Polyester over appropriate chemical pre-treatment.
Slat	- Width - Thickness - Material - Finish	25mm 0.21mm Coated Spring tempered Aluminium Alloy throughout yield strength 350mpa Oven-baked Polyester over appropriate chemical pre-treatment.
Tape	- Material - Construction - Rung Length - Rung Pitch	Polyester 1 Ply 28.5mm 28.0mm Non-ladder lock 20mm (Privasee) 18mm (Cimmerian)
Tilt Mechanism		Worm Drive Gear - Acetal/Polycarbonate Wand Control - Polycarbonate
Lifting Mechanism		Stainless Steel Roller and Knurled Brass Roller in Polycarbonate housing with Stainless Steel Wear Plates
Cord	- Diametre - Material	1.4mm Polyester
Colours		Wide range available

Feature Benefit

Privasee crimping
Allows for better closure.
Resulting in more light being blocked out.
Exclusive to Uniline.

Feature Benefit

Universal Spring Loaded fixing bracket
Provides a more secure fit and allows for more fixing points.

Feature Benefit

Australian Design Award
Assurance of the highest quality.



Privasee 25mm



*Continued on following page.

Tilt Rod	4.2mm Steel
Bearing Brackets	Polypropylene
Tape Roll	Polycarbonate
Installation Brackets	Zinc coated mild steel/polycarbonate
Head and Bottom Non End Caps	Polycarbonate

Feature	Private crimping
Benefit	Allows for better closure. Resulting in more light being blocked out. Exclusive to Uniline.
Feature	Universal Spring Loaded fixing bracket
Benefit	Provides a more secure fit and allows for more fixing points.
Feature	Australian Design Award
Benefit	Assurance of the highest quality.

