

ECO DAWN™  
BY UNILINE




# Technical Specifications - Eco Dawn™

## Roller • Panel Glide • Vertical

PRODUCT	WIDTH	TRANSLUCENT	BLOCKOUT	SCREEN	ROLLER	VERTICAL	ROMAN	PANEL GLIDE	RAILROAD YES/NO	ULTRAVIOLET PROTECTION
Eco Dawn™	2400mm		✓		✓	✓		✓	Yes	Excellent
PRODUCT	COMPOSITION		WEIGHT		THICKNESS		F/R RESULTS			
Eco Dawn™	100% Polyester Acrylic Coated		370gsm		0.39mm		AS-1530-2 *AS1530-3			
ULTRAVIOLET PROTECTION FACTOR	COLOUR FASTNESS		WARRANTY		AUSTRALIAN MADE					
50+	ISO 105-B02-1994 Xenon Arc Method >6-7		10 yrs		✓					



- ✓ BLOCKOUT
- ✓ ANTI FADE
- ✓ ACRYLIC COATED POLYESTER
- ✓ EASY CARE WIPE CLEAN SURFACE
- ✓ DUST RESISTANT
- ✓ LOW VOC'S
- ✓ ENERGY EFFICIENT MANUFACTURING



**Please Note:** \*Complies with the general requirements of the Building Code of Australia for fire hazard properties of materials in buildings. Not suitable for use in parts of buildings with special requirements. The information provided is based on typical values, please contact your representative for actual test results for project specifications. Railroading fabric is excluded from the Uniline 10 Year Guarantee.

AUS 1800 777 331  
NZ 09 273 5026

